

Package: orderly.sharepoint (via r-universe)

September 15, 2024

Title Sharepoint Driver for Orderly

Version 0.1.5

Description Store orderly reports on Sharepoint. Provides an orderly remote driver that can be used to share orderly reports using Sharepoint. You can use Sharepoint's access controls and use this to set up a lightweight way of using orderly within a team.

License MIT + file LICENSE

Encoding UTF-8

LazyData true

Language en-GB

Imports orderly1 (>= 1.7.0), spud (>= 0.1.5), zip

Suggests mockery, testthat

Remotes reside-ic/spud, orderly1=vimc/orderly@vimc-7135

RoxygenNote 7.0.2

Repository <https://vimc.r-universe.dev>

RemoteUrl <https://github.com/vimc/orderly.sharepoint>

RemoteRef master

RemoteSha 5e3a941cd0987b4eb4a39eaf9b8dc9ab9b5ace2

Contents

orderly_remote_sharepoint	2
Index	3

orderly_remote_sharepoint

Create an orderly remote based on Sharepoint

Description

Implements an orderly "remote" using Sharepoint as a backend. Use this within an orderly_config.yml configuration.

Usage

```
orderly_remote_sharepoint(url, site, path, name = NULL)
```

Arguments

url	Sharepoint URL
site	Sharepoint "site"
path	Path within the Sharepoint site. In our experience these often start with Shared Documents but your setup may vary.
name	Friendly name for the remote

Details

A configuration might look like:

```
remote:
  real:
    driver: orderly.sharepoint::orderly_remote_sharepoint
    args:
      url: https://example.sharepoint.com
      site: mysite
      path: Shared Documents/orderly/real
```

which would create a remote called real, using your group's Sharepoint hosted at https://example.sharepoint.com, on site mysite and within that site using path Shared Documents/orderly/real.

Currently authentication is interactive, or uses the values of environment variables SHAREPOINT_USERNAME and SHAREPOINT_PASS. Once we expose richer authentication approaches in spud that will be exposed here (RESIDE-162).

This function is not intended to be used interactively

Value

An orderly_remote_sharepoint object

An orderly_remote_sharepoint object, designed to be used by orderly. This function should however not generally be called by users directly, as it should be used within orderly_config.yml

Index

orderly_remote_sharepoint, [2](#)